

Document scanning. Done right.™

Regarded as ibml's most versatile scanners, the ImageTrac 5400 class scanners provide unique transaction processing benefits for users in a wide range of vertical markets.



Compared to other devices in their class, the ImageTrac 5400 class scanners provide unmatched image quality (at 200 and 300 DPI resolution), exceptional in-line intelligence and superior reliability and durability. The power of the ImageTrac 5400 class scanners makes them perfectly suited for high-volume sorting applications such as:

- Medical records scanning
- Mortgage processing
- Tax processing
- Claims processing
- Application processing
- Lockbox processing
- Back-file conversion
- Service bureau/shared services processing
- Digital mailroom

The ImageTrac 5400 class scanners are available in two speeds. The ImageTrac 5445 provides duplex scanning at up to 257 pages per minute while the ImageTrac 5475 provides duplex scanning at up to 429 pages per minute.\*

The ImageTrac 5400 class scanners also include features that make the most sophisticated jobs possible and easy to use, manage and maintain. The operator control center provides quick access to essential machine functions, simplifying the setup and processing of documents and increasing operator productivity. Because of their ease of use, a single person can operate multiple machines in certain applications.

#### BENEFITS:

- Increased productivity across the entire document capture process
- Business rule job development
- Faster processing windows
- Exceptional image quality
- Reduced document preparation requirements
- Streamlined operations for advanced processing requirements

#### FEATURES:

- Throughput speeds of 429 or 257 pages per minute\*
- Duplex camera imaging at 200 or 300 DPI resolution
- Mixed document scanning
- Bi-tonal, grayscale and color scanning
- Multi-feed detection
- Mechanical document de-skew and detection
- Complex decision and sort capabilities
- Up to 21 sort pockets
- User-friendly touch screen control

#### OPTIONS:

- Thick document detection
- Envelope detection
- Ultrasonic doubles detection
- Hardware barcode reader
- Dual ultrasonic doubles detection
- Pre- and post-image ink jet printer
- Hardware MICR reader
- JPEG 2000
- DocNetics® Suite

The ImageTrac 5400 class scanners also come standard with ibml's proven SoftTrac capture software (sold separately) for improved operational control, scanning accuracy and document processing. Built for the shared services approach, SoftTrac allows operators to manage scanning activities from an easy-to-use touch screen. It also provides the ability to manage scanning activities from a single console.

\*Based on 8.5" x 11" documents with a 2" gap at 200 DPI.

# ImageTrac 5400 Class Specifications

## RATED THROUGHPUT SPEEDS IN LANDSCAPE ORIENTATION

MODEL	RESOLUTION DPI	8.5X11 IN. PAGES/MINUTE	A4 PAGES/MINUTE	CHECKS PAGES/MINUTE	A6 PAGES/MINUTE
5445	200	257	263	568	440
	300	174	178	385	298
5475	200	429	438	947	733
	300	286	292	632	489

MAXIMUM DOCUMENT SIZE	297 mm (11.7 in.) x 432 mm (17 in.)
MINIMUM DOCUMENT SIZE	64 mm (2.5 in.) x 85 mm (3.25 in.)
PAPER THICKNESS AND WEIGHT	Standard feeder 45 g/m <sup>2</sup> to 200 g/m <sup>2</sup> ; Asian paper (rice paper) to card stock
FEEDER CAPACITY	1,500 sheets (20# bond paper)

ACCESSORIES		IMAGETRAC 5400
HARDWARE	BARCODE READER	Yes
	PATCH CODE READER	Yes
	SINGLE HEAD INK JET PRINTER	Pre and/or Post-Image
	MULTI-HEAD INK JET PRINTER	Pre and/or Post-Image
	MICR - E13B	Yes
	MICR - CMC7	Yes
	SORT POCKETS	A combination of pockets styles are available with full sort capabilities that support a wide range of document sizes
SOFTWARE	SOFTTRAC	Yes
	DOCNETICS SUITE	Yes, full

FEATURES		
MULTI-FEED DETECTION		Single or multiple ultrasonic sensor technology and/or friction multi-feed detection
COLOR TOUCH SCREEN CONTROL		Operator control via 21.5" wide screen color LCD panel touch screen
ILLUMINATION		Dual LED illumination patented technology
FILE FORMAT OUTPUT		JPEG (color/gray scale images); TIFF (black and white images); JPEG 2000
RESOLUTION	OPTICAL	300 dpi
	OUTPUT	Black and White/Color/Gray scale: 100 to 600 dpi; Scaling range limited to 1/2x to 2x from optical camera dpi.
IMAGE PROCESSING		DynamicTIFF Thresholding; Speckle Removal; Auto crop; Auto-Deskew; Image Rotation; Multi-image Output; Color Dropout, etc.
ENVIRONMENTAL FACTORS		RoHS compliant
ACOUSTICAL NOISE*		Operating mode 77.4db(A)
HEAT DISSIPATION*		6,000 to 15,000 BTUs/hour
OPERATING HUMIDITY		20% to 80% non-condensing (percent relative humidity)
OPERATING TEMPERATURE		50 to 90 degrees (F), 10 to 32 degrees (C)
SHIPPING/STORAGE TEMPERATURE		-22 to 140 degrees (F), -30 to 60 degrees (C)
ALTITUDE		Sea level to 10,000 ft (3,048 M)
ELECTRICAL REQUIREMENTS*		<b>United States:</b> 208V~, 2 Wire + GND25A 50/60 Hz; <b>European Union:</b> 230V~, 1 Wire + PE (single phase) 25A 50/60 Hz; <b>Japan:</b> 200V~, 2 Wire + GND25A 50/60 Hz <i>US Sites - Units shipped with power cord and 208-240V, NEMA #L6-30 connector</i> <i>Non US sites - Power cable supplied by customer to meet local electrical code</i>
APPROVAL AND PRODUCT CERTIFICATIONS*		ANSI/UL 60951-1 2nd Edition; CSA C22.2#60950-1; CENELEC EN 60950-1 2nd Edition; IEC 60950-1 2nd Edition; AS/NZS 60950-1; KN22; KN24; CE (self declaration); <b>Section 508:</b> VPAT on file.
MACHINE DIMENSIONS		Width: 32.38 inches; Length: 134.145 inches; Height: 48.33 inches Dimensions are for a 4 frame scanner; additional frames will vary the length.
WEIGHT		Feeder frame: 226 lbs; Front camera frame: 284 lbs; Escalator frame: 195 lbs; Pocket frame: 235 lbs
HOST		Embedded Controller

Specifications are subject to change without notice.

Minimum gap and throughput will vary based on the specific application processing requirements.